

The Tvilight IoT Gateway is a network interface device which synchronises Tvilight outdoor lighting controllers and the street lighting management software (Tvilight CityManager LMS or similar third-party software).

The IoT Gateway has an in-built radio module for wireless network configuration, commissioning, and maintenance. It can reliably communicate with a large number of devices spread across large distances. In-built smart monitoring tools notify users about the status of the lamps and the network (via CityManager LMS or other software).

Several Internet connectivity options offer robustness and flexibility to the end-customer. Furthermore, it supports industry standard protocols allowing for an easy integration with other systems and networks.

The Gateway encloses advanced industrial components for optimised performance worldwide.

Designed in the Netherlands  Made in Europe 



Technical Specifications

HARDWARE

Integrated product	In-built power supply, 2.4 GHz wireless network communication, server communication (SIM-card, Ethernet, Wi-Fi). SIM-card provided by Tvilight with global coverage, or by customer (requires 1GB monthly data subscription).
Input voltage	Universal 100 – 240V AC, 50/60 Hz.
Power Consumption	<8W (average)
Processor	High-performance, industrial grade ARM Cortex-A9 CPU, 1 GHz.
Data storage	Micro SD-Card / On-board NAND flash
Electrical protection	Class II: overload, short-circuit and over-temperature protection
Electrical safety	Galvanic isolation between high-voltage and low-voltage terminals
Operating conditions	-20°C to +60°C Operating; -40°C to +85°C Storage; 20% to 90%, Rh non-Condensing
Antenna	Integrated internally for 2.4 GHz wireless, Wi-Fi and GSM
Connectors	1x Ethernet port (10/100, RJ45) 1x Micro-SD memory card slot (max. 32 GB) 1x Push insert standard SIM-card bay (25mm x 15mm) 2x UfL Antenna connector (2.4 GHz wireless, Wi-Fi) 1x SMA-F Antenna connector (2G/ 3G modem)
Product mounting options	Pole or wall mounting. Please observe installation manual and Tvilight installation guidelines with respect to radio connectivity.
Housing	IP67, UL94V0
Dimension	230 mm x 130 mm x 90 mm
Manufacturing	ISO 9001: 2008, Made in Europe
Compliances	CE, CB, EN61547, EN55015, EN60950-1, EN 301 489-1/17, EN 300 328, RoHS. RF transceiver compliant with US (FCC), Canadian (IC), European (ETSI), and Japanese (Telec) standards.

INTERNET COMMUNICATION

Server communication	Cat 4 / GSM FDD Bands 1, 3, 5, 7, 8, 20 UMTS/DC-HSPA+ 850/900/1900/2100 GSM 850/900/1800/1900 GPRS & EDGE Class 12 Additional Ports: Ethernet and Wi-Fi
Network security	128-bit AES encryption between devices and IoT Gateway Certificate-based secure WebSocket and VPN connection between Gateway and Server
Functions	Real-time monitoring of devices and network; Several Internet connectivity options using Ethernet, Wi-Fi and GSM; SNTP time-sync between IoT Gateway and devices; Regular logging of the system operation (selectable time interval); Real-time connection between Gateway and CityManager LMS; Remote debugging of IoT Gateway and devices; Over-the-air update for IoT Gateway and devices (software and firmware)
Remote monitoring	CityManager LMS (or third-party software via API) enables remote management, monitoring, control, and configuration of lamps on individual and group levels.

WIRELESS COMMUNICATION

Wireless network	2.4 GHz IEEE 802.15.4 self-healing and self-forming wireless network depending on variant: +9.5dBm max. transmit power, -96dBm receiver sensitivity, up to 150-meter open field range or + 22dBm transmit power, -100dBm max. receiver sensitivity, up to 1-km open field range Up to 250 kbps microcontroller RF data rate.
Device to Gateway ratio	200:1
Product compatibility	Wireless compatibility with SkyLite Prime, SkyLite External, CitySense Plus and CityManager LMS
Warranty	Standard 2 years limited warranty. Extended warranty available. Warranty subject to proper use of installation and application manuals. To protect the equipment from damage, over-voltage protector or surge protector must be used in case of voltages exceeding the rated voltages listed. See the protectors manual for installation guidelines.
Application	Outdoor street lighting. Area lighting

AVAILABLE VARIANTS

Order code	Description
PR172141	Gateway RF, 100-240V